

10/11/00

JC951 U.S. PTO

0-13-00

A

Please type a plus sign (+) inside this box → ☐Approved for use through 10/31/2002 OMB 0651-0032
U.S. Patent and Trademark Office, U S DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO/SB/05 (08-00)

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	164.1012.01
First Inventor	Subir VARMA
Title	Contention Control with State Machine
Express Mail Label No.	EL 524 780 636 US

JC951 U.S. PTO

09/689243

10/11/00

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☐ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☐ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification [Total Pages]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets]
5. Oath or Declaration [Total Pages]
 - a. ☐ Newly executed (original or copy)
Copy from a prior application (37 CFR 1.63 (d))
 - b. ☐ (for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b)
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO:Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or
Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement ☐ Power of
(when there is an assignee) Attorney
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☒ Other: Certificate of Mailing

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____

Prior application information: Examiner _____ Group / Art Unit _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS☒ Customer Number or Bar Code Labelor ☐ Correspondence address below

PATENT TRADEMARK OFFICE

Name			
Address			
City	State	Zip Code	
Country	Telephone	Fax	

Name (Print/Type)	Steven A. Swernofsky	Registration No. (Attorney/Agent)	33,040
Signature			Date October 11, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.



22883

PATENT TRADEMARK OFFICE

164.1012.01

Certificate of Mailing (37 C.F.R. § 1.10)

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited with the United States Postal Services on the date shown below as "Express Mail" (Post Office to Addressee) in an envelope addressed to the Honorable Assistant Commissioner for Patents and Trademarks, Box Patent Application, Washington, D.C. 20231.

Mailing Label No. EL 524 780 636 USDate of Deposit: October 11 , 2000Arlette Malhas
Printed Name*Arlette Malhas*
Signature

Documents enclosed:

- Utility Patent Application Transmittal Form;
- Specification (25) pages;
- Claims (5) pages;
- Abstract (1) pages;
- Drawings (2) pages;
- Return post card; and
- Certificate of Express Mailing.

001101 689243



22883

PATENT TRADEMARK OFFICE

164.1012.01

This application is submitted in the name of the following inventors:

<u>Inventor</u>	<u>Citizenship</u>	<u>Residence City and State</u>
Subir VARMA	United States	San Jose, CA

The assignee is *Aperto Networks, Inc.*, a corporation having an office at 1637 South Main Street, Milpitas CA 95035.

Title of the Invention

Contention Control with State Machine

Background of the Invention

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

1. Field of the Invention

This invention relates to point-to-multipoint communication. In particular, the invention relates to control of contention for data slots by customer premises equipment in a wireless point-to-multipoint communication system.

2. *Description of the Related Art*

In a point-to-multipoint network, plural customer provided equipment (CPEs) communicate bidirectionally with a base station controller (BSC) in a cell. Several CPEs can share a single channel for communicating with the BSC. The CPEs and the BSC use time division duplexing (TDD) to facilitate the bidirectional aspect of the communication. The CPEs and the BSC use time division multiple access (TDMA) to facilitate sharing of a channel among plural CPEs.

In TDMA, the BSC grants data slots to the CPEs. Because multiple CPEs share a limited number of data slots, the CPEs and the BSC must negotiate data slot assignments through a process called contention.

In contention, CPEs that have upstream data to send to the BSC first send a short request (REQ) message to the BSC. The BSC responds with a grant of a data slot for use by the CPE.

Problems can arise in contention. First, two CPEs might simultaneously try to use a single request slot to request data slots. This situation is called collision. When collisions occur, neither CPE's request message successfully reaches the BSC. Second, if many request slots are defined so as to reduce a number of collisions and so as to facilitate requests by a large number of CPEs, too much of available bandwidth can be used up by contention traffic. As a result, data throughput can be unacceptably decreased.

1 One technique used in the prior art to reduce contention traffic is called
2 piggybacking. In piggybacking, a CPE first requests a data slot. When the data slot is granted by
3 the BSC, the CPE sends data packets upstream. The CPE attaches a size of its current data
4 backlog to a header for one of the data packets. As a result, whenever the backlog is non-zero,
5 the BSC knows to grant a data slot to the CPE without the CPE having to send a REQ message.
6 Thus, contention traffic is reduced.

7
8 Unfortunately, piggybacking is only effective if upstream traffic from the CPE is
9 of the bursty type, so that the CPE needs to make only one contention request per burst.

10 However, some important traffic sources are non-bursty. Examples of non-bursty traffic include
11 traffic generated by online games and voice sources. Even ordinary Internet traffic running over
12 TCP becomes non-bursty when a communication link is in heavy traffic. In the presence of
13 non-bursty traffic, the piggyback scheme breaks down, and an excessive number of contention
14 requests are sent upstream.

15 16 Summary of the Invention 17

18 In view of the foregoing, further reducing contention traffic is desirable, especially
19 for non-bursty traffic. The invention addresses this need by using a new state machine to control
20 a contention state for a communication link between a base station controller and customer
21 premises equipment in point-to-multipoint communication. According to the invention, the state
22 machine includes a grant pending absent state in which the customer premises equipment is
23 polled with a unicast request slot. During the grant pending absent state, the customer premises
24 equipment sends no upstream data to the base station controller but can use the unicast request
25 slot to request a data slot for sending upstream data to the base station controller.

1
2 By virtue of the grant pending absent state, the customer premises equipment can
3 request a data slot without entering into contention and generating excess contention traffic.
4 After a suitable delay without more data being received to send upstream, the state machine can
5 exit the grant pending absent state. This delay preferably is long enough for receipt of new non-
6 bursty data for a communication, for example 50 ms.

7
8 The state machine preferably also includes an idle state in which the customer
9 premises equipment awaits arrival of data packets to send as upstream data to the base station
10 controller, a deferring state in which the customer premises equipment requests grant of a data
11 slot for sending upstream traffic to the base station controller and if necessary defers contending
12 for the data slot so as to avoid collisions with other customer premises equipment, and a grant
13 pending state in which the customer premises equipment awaits and receives grant of the data
14 slot for sending upstream data to the base station controller and sends upstream data to the base
15 station controller after grant of the data slot.

16
17 In a preferred embodiment of the invention, the customer premises equipment
18 uses piggybacking to request grant of a next data slot while sending upstream data to the base
19 station controller. Use of piggybacking along with the grant pending absent state has been found
20 to decrease drastically contention traffic.

21
22 Preferably, the state machine enters the deferring state upon arrival of data packets
23 to send as upstream data to the base station controller. In the preferred embodiment, the state
24 machine enters the grant pending state after the deferring state, returns to the deferring state if a
25 collision occurs, and remains in the grant pending state when sending upstream data to the base

1 station controller with piggybacking. The state machine preferably enters the grant pending
2 absent state after the customer premises equipment has sent upstream data to the base station
3 controller in the grant pending state.

4
5 The state machine according to the invention preferably also includes an
6 unsolicited grant pending state in which the customer premises equipment receives grant of the
7 data slot for sending upstream data to the base station controller and sends upstream data to the
8 base station controller after grant of the data slot, without having requested the data slot. The
9 state machine preferably further includes an unsolicited grant pending absent state in which the
10 customer premises equipment is polled with the unicast request slot. During the unsolicited grant
11 pending absent state, the customer premises equipment sends no upstream data to the base station
12 controller but can use the unicast request slot to request the data slot for sending upstream data to
13 the base station controller. Preferably, the state machine enters the unsolicited grant pending
14 absent state after the customer premises equipment has sent upstream data to the base station
15 controller in the unsolicited grant pending state.

16
17 The invention can be embodied in a method for controlling communication using
18 the state machine described above, as well as in software and/or hardware such as a base station
19 controller and/or customer premises equipment that implements the method, and in various other
20 embodiments.

21
22 This brief summary has been provided so that the nature of the invention may be
23 understood quickly. A more complete understanding of the invention may be obtained by
24 reference to the following description of the preferred embodiments thereof in connection with
25 the attached drawings.

Brief Description of the Drawings

Figure 1 is a block diagram of a wireless communication system according to the invention in which a base station controller communicates with one or more customer premises equipment according to the invention.

Figure 2 is a flow chart of a state machine according to the invention.

Description of the Preferred Embodiment

Related Applications

Inventions described herein can be used in conjunction with inventions described in the following documents.

U.S. Patent Application Serial No. 09/475,642, Express Mail Mailing No. EL524780018US, filed December 30, 1999 in the names of Reza Majidi-Ahy, Subir Varma, Khuong Ngo, Jean Fuentes and Paul Trong, attorney docket number 164.1002.01, titled "Adaptive Link Layer for Point to Multipoint Communication System."

U.S. Patent Application Serial No. 09/475,716, Express Mail Mailing No. EL524780021US, filed December 30, 1999 in the names of Reza Majidi-Ahy, Joseph Hakim, and Subir Varma, attorney docket number 164.1003.01, titled "Integrated Self-Optimizing Multi-Parameter and Multi-Variable Point to Multipoint Communication System."

1
2 U.S. Patent Application Serial No. 09/540,674, Express Mail Mailing No.
3 EL524781512US, filed March 31, 2000, in the name of Reza Majidi-Ahy, attorney docket
4 number 164.1001.01, titled "Robust Topology Wireless Communication Using
5 Broadband Access Points."

6
7 U.S. Patent Application Serial No. 09/604,784, Express Mail Mailing No.
8 EL524781225US, filed June 26, 2000 in the name of Reza Majidi-Ahy, attorney docket
9 number 164.1010.01, titled "High-Capacity Scalable Integrated Wireless Backhaul for
10 Broadband Access Networks."

11
12 and

13 U.S. Patent Application Serial No. 09/475,716, Express Mail Mailing No.
14 EL524780021US, filed December 30, 1999 in the names of Reza Majidi-Ahy, Joseph
15 Hakim, and Subir Varma, attorney docket number 164.1003.01, titled "Integrated, Self-
16 Optimizing, Multi-Parameter/Multi-Variable Point-to-Multipoint Communication System
17 [II]."
18

19 Each of these documents is hereby incorporated by reference as if fully set forth
20 herein. This application claims priority of each of these documents. These documents are
21 collectively referred to as the "Incorporated Disclosures."

22
23 *Lexicography*
24

25 The following terms refer or relate to aspects of the invention as described below.
26 The descriptions of general meanings of these terms are intended to be illustrative, not limiting.

1 **base station controller (BSC)** — in general, a device for performing coordination and
2 control for a wireless communication cell. There is no particular requirement that the base
3 station controller must be a single device; in alternative embodiments, the base station
4 controller can include a portion of a single device, a combination of multiple devices, or
5 some hybrid thereof.

6
7 **communication link** — in general, an element for sending information from a sender to a
8 recipient. Although in a preferred embodiment the communication links referred to are
9 generally wireless line of sight point to point communication links, there is no particular
10 requirement that they are so restricted.

11
12 **customer premises equipment (CPE)** — in general, a device for performing
13 communication processes and tasks at a customer location, and operating in conjunction
14 with the base station controller within a wireless communication cell. There is no
15 particular requirement that the customer premises equipment must be a single device; in
16 alternative embodiments, the customer premises equipment can include a portion of a
17 single device, a combination of multiple devices, or some hybrid thereof.

18
19 As noted above, these descriptions of general meanings of these terms are not
20 intended to be limiting, only illustrative. Other and further applications of the invention,
21 including extensions of these terms and concepts, would be clear to those of ordinary skill in the
22 art after perusing this application. These other and further applications are part of the scope and
23 spirit of the invention, and would be clear to those of ordinary skill in the art, without further
24 invention or undue experimentation.

25
26 *System Context*

1
2 The context of the invention is similar to that of the Incorporated Disclosures.

3
4 A system using point-to-multipoint communication in a wireless communication
5 system operates as part of a system in which devices coupled to a network (such as a computer
6 network) send messages, route and switch messages, and receive messages. In a preferred
7 embodiment, devices coupled to (and integrated with) the network send, route, and receive these
8 messages as sequences of packets, each of which has a header including delivery information and
9 a payload including data. In a preferred embodiment, packet format conforms to the OSI model,
10 in which an application protocol (layer 5, such as FTP) uses a transport protocol (layer 4, such as
11 TCP), which uses a network protocol (layer 3, such as IP), which uses a media access control
12 (MAC) protocol (layer 2), which uses a physical transport technique (layer 1).

13
14 *System Elements*

15
16 Fig. 1 is a block diagram of a wireless communication system according to the
17 invention in which a base station controller communicates with one or more customer premises
18 equipment according to the invention.

19 System 10 includes wireless communication cell 11 (or a portion thereof), base
20 station controller (BSC) 12, and one or more customer premises equipment (CPE) 13.

21
22 Wireless communication cell 11 preferably includes a generally hexagon-shaped
23 region of local surface area, such as might be found in a metropolitan region. Use of generally
24 hexagon-shaped regions is known in the art of wireless communication because hexagonal
25 regions are able to tile a local region with substantially no gaps. Although in a preferred
26 embodiment wireless communication cell 11 includes a generally hexagon-shaped region, no

1 particular requirement exists for using that particular shape; in alternative embodiments, another
2 shape or tiling of the local surface area may be useful.
3

4 In Fig. 1, a portion of cell 11 includes a generally triangular-shaped region of local
5 surface area, herein called a “sector.” Sectors 14 preferably are disposed so that a set of six
6 sectors 14 combine to form single cell 11. Thus, BSC 12 preferably is disposed at or near one
7 corner of one of sectors 14, while CPEs 13 are disposed within the sectors.
8

9 Although the invention is primarily described with regard to interactions that
10 occur between BSC 12 and a single CPE 13 in a single sector 14, substantial applications of the
11 invention exist for interactions across multiple sectors within a cell, and to interaction across
12 sectors in multiple cells. Substantial applications of the invention with regard to multiple
13 sectors, both within single cell and among multiple cells, would be clear to those skilled in the art
14 of wireless communication after perusal of this application, and would not require undue
15 experimentation or further invention.
16

17 BSC 12 preferably includes a processor, program and data memory, mass storage,
18 and one or more antennas for sending or receiving information using wireless communication
19 techniques.
20

21 Similar to BSC 12, each CPE 13 preferably includes a processor, program and
22 data memory, mass storage, and one or more antennas for sending or receiving information using
23 wireless communication techniques.
24

25 In system 10, plural CPEs 13 communicate bidirectionally with BSC 12. Several
26 CPEs 13 can share a single channel for communicating with BSC 12. BSC 12 and CPEs 13

1 preferably use time division duplexing (TDD) to facilitate the bidirectional aspect of the
2 communication. BSC 12 and CPEs 13 preferably use time division multiple access (TDMA) to
3 facilitate sharing of a channel among plural CPEs 13.

4
5 In TDMA, BSC 12 grants data slots to CPEs 13. Because multiple CPEs 13 share
6 a limited number of data slots, CPEs 13 and BSC 12 must negotiate data slot assignments through
7 a process called contention.

8
9 In contention, CPEs 13 that have upstream data to send to BSC 12 first send a
10 short request (REQ) message to BSC 12. The BSC responds with a grant of a data slot for use by
11 the CPE.

12
13 Problems can arise in contention. Plural CPEs 13 might simultaneously try to use
14 a single request slot to request data slots. This situation is called collision. When collisions
15 occur, none of the CPE's request messages successfully reach BSC 12. Those CPEs 13 have to
16 re-send their REQ messages. In order to try to allow REQ traffic to clear, CPEs 13 according to
17 the invention can defer re-sending REQ messages for some period of time when collisions occur.

18
19 If many request slots are defined so as to reduce a number of collisions and so as
20 to facilitate requests by a large number of CPEs 13, or if too many REQ messages have to be re-
21 sent, too much of available bandwidth can be used up by contention traffic. As a result, data
22 throughput can be unacceptably decreased.

23
24 One technique used in the prior art to reduce contention traffic is called
25 piggybacking. In piggybacking, CPE 13 first requests a data slot. When the data slot is granted
26 by BSC 12, CPE 13 sends data packets upstream. CPE 13 attaches a size of its current data

backlog to a header for one of the data packets. As a result, whenever the backlog is non-zero, BSC 12 knows to grant a data slot to CPE 13 without CPE 13 having to send a REQ message. Thus, contention traffic is reduced.

Unfortunately, piggybacking is only effective if upstream traffic from CPE 13 is of the bursty type, so that CPE 13 needs to make only one contention request per burst. However, some important traffic sources are non-bursty. Examples of non-bursty traffic include traffic generated by online games and voice sources. Even ordinary Internet traffic running over TCP becomes non-bursty when a communication link is in heavy traffic. In the presence of non-bursty traffic, the piggyback scheme breaks down, and an excessive number of contention requests are sent upstream.

The invention attempts to reduce contention traffic by using a new state machine to control a contention state for a communication link between a base station controller and customer premises equipment in point-to-multipoint communication. The state can be controlled by the CPE, the BSC, or both.

Fig. 2 is a flow chart of a state machine according to the invention.

Briefly, according to the invention, the state machine includes a grant pending absent state in which the customer premises equipment is polled with a unicast request slot. During the grant pending absent state, the customer premises equipment sends no upstream data to the base station controller but can use the unicast request slot to request a data slot for sending upstream data to the base station controller.

1 By virtue of the grant pending absent state, the customer premises equipment can
2 request a data slot without entering into contention and generating excess contention traffic.
3 After a suitable delay without more data being received to send upstream, the state machine can
4 exit the grant pending absent state. This delay preferably is long enough for receipt of new non-
5 bursty data for a communication, for example 50 ms.

6
7 In more detail, Fig. 2 shows a state machine that includes idle state 20, deferring
8 state 21, grant pending state 22, grant pending absent state 23, unsolicited grant pending state 24,
9 and unsolicited grant pending absent state 25. While the particular states shown in Fig. 2 are
10 representative of a preferred embodiment of the invention, the invention also can utilize state
11 machines that do not include all of these states and/or that include additional states.

12
13 Idle state 20 is a waiting state in which the customer premises equipment awaits
14 arrival of data packets to send as upstream data to the base station controller.

15
16 Upon arrival of data to be sent as upstream data, the state machine transitions to
17 deferring state 21. The state machine also can transition to unsolicited grant pending state 24
18 upon receipt of an unsolicited grant of a data slot from BSC 24, as discussed below.

19
20 In deferring state 21, CPE 13 sends a REQ message to BSC 12. The state
21 machine then transitions to grant pending state 22. However, if no grant is received from BSC
22 12 in grant pending state 22 before a timeout, the state machine returns to deferring state 21, as
23 discussed below.

24
25 One possible reason for non-receipt of a grant is a collision with another CPE 13.
26 Thus, deferral is needed, and CPE 13 defers sending a new REQ message for a period of time.

1 The CPE then sends the new REQ message. In a preferred embodiment, if another collision
2 occurs, CPE 13 again defers sending another REQ message. This process preferably continues
3 until the REQ messages gets through to BSC 12 (as evidenced by receipt of a grant) or until an
4 error is generated (not shown).

5
6 Preferably, each time CPE 13 defers sending a REQ message, the period of
7 deferral roughly doubles, with a random factor included to try to avoid deferring in synch with
8 another CPE. Thus, in deferring state 21, CPE 13 defers contending for a data slot so as to avoid
9 collisions with other customer premises equipment.

10
11 In grant pending state 22, CPE 13 awaits and receives grant of the data slot for
12 sending upstream data to the base station controller and sends upstream data to the base station
13 controller after grant of the data slot. However, if a grant is not received before a timeout, the
14 CPE concludes that a collision or some other error has occurred, and the state machine returns to
15 deferring state 21.

16
17 Preferably, in grant pending state 22, CPE 13 uses piggybacking to request grant
18 of a next data slot while sending upstream data to BSC 12. When CPE 13 sends the last data in
19 its backlog, that data preferably is sent without piggybacking. The state machine then transitions
20 to grant pending absent state 23 according to the invention.

21
22 During grant pending absent state 23, CPE 13 sends no upstream data to BSC 12.
23 No grant is pending because piggybacking was not used in the previous transmission of data to
24 BSC 12 (hence the name of the state). Rather, CPE 13 is periodically (e.g., every 10 ms) polled
25 by BSC 12 with a unicast request slot. CPE 13 can use this unicast request slot to request a data
26 slot for sending upstream data to the base station controller. Thus, if more data is received by

1 CPE 13 to send upstream to BSC 12, CPE 13 can request a data slot without going through
2 contention, thereby reducing contention traffic.

3
4 In some circumstances, the reduction in contention traffic can be drastic, for
5 example by an order of magnitude. Of course, the invention is not limited to such circumstances
6 and is not limited to such drastic reductions in contention traffic.

7
8 Upon grant of a data slot for sending new data to BSC 12, CPE 13 returns to grant
9 pending state 22.

10
11 If no new data is received by CPE 13 before a timeout in grant pending absent
12 state 23, the state machine returns to idle state 20. A timeout of 50 ms has been found to work
13 well.

14
15 In some circumstances, BSC 12 can grant a data slot to CPE 13 without the CPE
16 having requested the data slot. For example, if the communication between BSC 12 and CPE 13
17 is a voice communication, BSC 12 can predict that CPE 13 will need data slots. BSC 12 can
18 grant those data slots to CPE 13 without CPE 13 having to request them. Such a grant is an
19 unsolicited grant.

20
21 Accordingly, the preferred embodiment of the state machine according to the
22 invention also includes unsolicited grant pending state 24 and unsolicited grant pending absent
23 state 25. These states correspond to grant pending state 22 and grant pending absent state 23,
24 respectively, with the exception that they are entered when an unsolicited grant occurs.

1 Thus, in unsolicited grant pending state 24, CPE 13 receives grant of the data slot
2 for sending upstream data to the base station controller and sends upstream data to the base
3 station controller after grant of the data slot, without having requested the data slot.
4

5 In unsolicited grant pending absent state 25, CPE 13 is polled with the unicast
6 request slot. During unsolicited grant pending absent state 25, CPE 13 sends no upstream data to
7 BSC 12 but can use the unicast request slot to request the data slot for sending upstream data to
8 BSC 12. The state machine enters unsolicited grant pending absent state 25 after CPE 12 has
9 sent upstream data to BSC 12 in unsolicited grant pending state 24.

10 Pseudo-code for implementing the preferred embodiment of the invention
11 substantially as discussed above is included in a technical appendix to this application.
12
13

14 *Alternative Embodiments*

15 The invention can be embodied in a method for controlling communication using
16 the state machine described above, as well as in software and/or hardware such as a BSC and/or a
17 CPE that implements the method, and in various other embodiments.
18
19

20 In the preceding description, a preferred embodiment of the invention is described
21 with regard to preferred process steps and data structures. However, those skilled in the art
22 would recognize, after perusal of this application, that embodiments of the invention may be
23 implemented using one or more general purpose processors or special purpose processors
24 adapted to particular process steps and data structures operating under program control, that such
25 process steps and data structures can be embodied as information stored in or transmitted to and
26 from memories (e.g., fixed memories such as DRAMs, SRAMs, hard disks, caches, etc., and

1 removable memories such as floppy disks, CD-ROMs, data tapes, etc.) including instructions
2 executable by such processors (e.g., object code that is directly executable, source code that is
3 executable after compilation, code that is executable through interpretation, etc.), and that
4 implementation of the preferred process steps and data structures described herein using such
5 equipment would not require undue experimentation or further invention.

6
7 Furthermore, although preferred embodiments of the invention are disclosed
8 herein, many variations are possible which remain within the content, scope and spirit of the
9 invention, and these variations would become clear to those skilled in the art after perusal of this
10 application.

TECHNICAL APPENDIX

Pseudo-code copyright 2000 Aperto Networks, Inc.

4.1 State: Idle

ContentionWindow = 0;

Wait for !QueueEmpty;

/* The CPE may get an unicast REQ slot in the idle state. */

/* In this case it returns the current reqWin value */

if (unicast REQ SID == mySID) /* Polling case */

{

 Transmit REQ in reservation;

 Tx_slot = slot;

 PrevREQ = NonContREQ;

}

if (NormalGrantId == mySID)

 Utilize Normal Grant();

else if (UnsolicitedGrantId == mySID)

{

 Utilize Unsolicited Grant();

 Go to State Unsolicited Grant Pending;

}

/* EPDU Arrives */

Enqueue();

CalculateDefer();

Go to State Deferring

4.2 State: Deferring

```

1  if (UnsolicitedGrantId == mySID) /* Unsolicited Grant Service */
2
3  {
4      Utilize Unsolicited Grant();
5      Go to State Unsolicited Grant Pending;
6  }
7  else if (NormalGrantId == mySID)
8      Utilize Normal Grant();
9  else if (unicast REQ SID == mySID) /* Polling case */
10 {
11     Transmit REQ in reservation;
12     Tx_slot = slot;
13     Go to Grant Pending;
14     PrevREQ = NonContREQ;
15 }
16 else
17 {
18     for (REQ Transmit Opportunity) /* Contention based REQ transmission */
19     {
20         if (Defer != 0)
21             Defer = Defer - 1;
22         else /* Defer = 0 */
23         {
24             if (Number of SIDs in CPE, with Defer = 0 is greater than 1)
25                 choose one SID at random;
26             if (my SID chosen)

```

```

1          {
2              Transmit REQ in contention;
3              Tx_slot = slot;
4              RTxTime = time_now;
5              PrevREQ = ContREQ;
6              Go to Grant Pending;
7          }
8      }
9  }

```

4.3 State: Grant Pending

```

10      Wait for next MAP;
11      Move ACK pointer as per ACK field in MAP;
12      The next byte to transmit is set as per ACK/NACK flag and
13      Sequence Number in the ACK
14      if (Flush EPDU field set)
15      {
16          Flush HOL EPDU;
17          Go to Idle;
18      }
19      if (unicast REQ SID == mySID) /* Polling case */
20      {
21          Transmit REQ in reservation;
22          Tx_slot = slot;
23          PrevREQ = NonContREQ;

```

```

1      }
2      if (Normal GrantId == mySID)
3          Utilize Normal Grant();
4      else if (Unsolicited GrantId == mySID)
5      {
6          Utilize Unsolicited Grant();
7          Go to State Unsolicited Grant Pending;
8      }
9      else if (implicit collision indication received)
10         Retry();
11     else /* Error Condition: BSC did not give grant that CPE is expecting */
12         Go to Idle;

```

4.4 State: Grant Pending Absent

```

15     if (First Time Entering State)
16         Count = GrantPendingWait;
17     else
18         --Count;
19     if (unicast REQ SID == mySID) /* Polling case */
20     {
21         Transmit REQ in reservation;
22         Tx_slot = slot;
23         PrevREQ = NonContREQ;
24     }

```

4.5 State: Unsolicited Grant Pending

```

1  if (unicast REQ SID == mySID) /* Polling case */
2  {
3      Transmit REQ in reservation;
4      Tx_slot = slot;
5      PrevREQ = NonContREQ;
6  }
7  if (Unsolicited GrantId == mySID)
8  {
9      Utilize Unsolicited Grant();
10     Remain in State Unsolicited Grant Pending;
11 }
12 if (Last Unsolicited Grant)
13     Go to state Idle;
14
15 4.6 State: Unsolicited Grant Absent
16 if (First Time Entering State)
17     Count = UnsolicitedGrantPendingWait;
18 else
19     --Count;
20 if (unicast REQ SID == mySID) /* Polling case */
21 {
22     Transmit REQ in reservation;
23     Tx_slot = slot;
24     PrevREQ = NonContREQ;
25 }
26

```


4.7 Function: CalculateDefer()

```

1  if (ContentionWindow < Start)
2
3      Window = Start;
4
5  if (ContentionWindow > End)
6
7      Window = End;
8
9  Defer = Random[2^ContentionWindow];

```

4.8 Function: Utilize Normal Grant()

```

10  if (Grant Size == 0) /* Scheduler not able to make grant during this frame */
11
12      Go to Grant Pending;
13
14  else /* Grant Size > 0 */
15
16      {
17
18          while (GrantSID == mySID) /* Multiple Grants in MAP */
19
20              {
21
22                  Extract Indicated number of bytes from SID queue;
23
24                  Confirm that these bytes fit in the tick space allocated;
25
26                  piggyback size = RequestWindow;
27
28                  Transmit WPDU with Sequence Number Field set as per MAP and
29
30                  Piggyback field set as above;
31
32              }
33
34          if (piggyback size > 0)
35
36              {
37
38                  Go to Grant Pending;
39
40                  RTxTime = time_now;
41
42                  PrevREQ = NonCOnTREQ;
43
44              }

```

```

1      else /* No more bytes left in SID queue */
2          Go to GrantPendingWait;
3      }

```

```

4
5  4.9 Function: Utilize Unsolicited Grant()
6  while (GrantSID == mySID) /* Multiple Grants in MAP */
7  {
8      Extract Indicated number of bytes from SID queue;
9      if (#bytes == 0)
10         Tx only WPDU header;
11     else
12     {
13         Confirm that these bytes fit in the tick space allocated;
14         piggyback size = RequestWindow;
15         Transmit WPDU with Sequence Number Field set as per MAC and
16         Piggyback field set as above;
17     }
18 }

```

```

19
20 4.10 Function: Retry()
21 Retries = Retries + 1;
22 if (Retries > 16)
23 {
24     Discard HOL EPDU;
25     Go to Idle;
26 }

```

```
1   ContentionWindow = ContentionWindow + 1;  
2   CalcDefer();  
3   Go to Deferring;  
4  
5   4.11 Function: Enqueue()  
6   Enqueue EPDU to tail of queue;  
7   RequestWindow = RequestWindow + Size of EPDU;
```

0968943 "10.1.100
007.107" 2428960

1 Claims

2
3 What is claimed is:

4
5 1. A method of controlling a contention state for a communication link between a
6 base station controller and customer premises equipment in point-to-multipoint communication,
7 comprising the step of:

8 controlling the contention state using a state machine, the state machine including
9 a grant pending absent state in which the customer premises equipment is polled with a unicast
10 request slot, wherein during the grant pending absent state, the customer premises equipment
11 sends no upstream data to the base station controller but can use the unicast request slot to
12 request a data slot for sending upstream data to the base station controller.

13
14 2. A method as in claim 1, wherein the state machine further includes an idle state
15 in which the customer premises equipment awaits arrival of data packets to send as upstream
16 data to the base station controller.

17
18 3. A method as in claim 2, wherein the state machine further includes a deferring
19 state in which the customer premises equipment requests grant of a data slot for sending
20 upstream traffic to the base station controller and if necessary defers contending for the data slot
21 so as to avoid collisions with other customer premises equipment.

22
23 4. A method as in claim 3, wherein the state machine further includes a grant
24 pending state in which the customer premises equipment awaits and receives grant of the data
25 slot for sending upstream data to the base station controller and sends upstream data to the base
26 station controller after grant of the data slot.

1
2 5. A method as in claim 4, wherein in the grant pending state, the customer
3 premises equipment uses piggybacking to request grant of a next data slot while sending
4 upstream data to the base station controller.
5

6 6. A method as in claim 5, wherein the state machine enters the deferring state
7 upon arrival of data packets to send as upstream data to the base station controller,

8 wherein the state machine enters the grant pending state after the deferring state,
9 returns to the deferring state if a collision occurs, and remains in the grant pending state when
10 sending upstream data to the base station controller with piggybacking, and

11 wherein the state machine enters the grant pending absent state after the customer
12 premises equipment has sent upstream data to the base station controller in the grant pending
13 state.
14

15 7. A method as in claim 6, wherein the state machine further includes an
16 unsolicited grant pending state in which the customer premises equipment receives grant of the
17 data slot for sending upstream data to the base station controller and sends upstream data to the
18 base station controller after grant of the data slot, without having requested the data slot.

19 8. A method as in claim 7, wherein the state machine further includes an
20 unsolicited grant pending absent state in which the customer premises equipment is polled with
21 the unicast request slot,

22 wherein during the unsolicited grant pending absent state, the customer premises
23 equipment sends no upstream data to the base station controller but can use the unicast request
24 slot to request the data slot for sending upstream data to the base station controller, and

1 wherein the state machine enters the unsolicited grant pending absent state after
2 the customer premises equipment has sent upstream data to the base station controller in the
3 unsolicited grant pending state.

4
5 9. Customer premises equipment that communicates over a communication link
6 with a base station controller in point-to-multipoint communication, comprising:

7 a transceiver, and

8 a controller that controls a contention state for communicating over the
9 communication link via the transceiver, the controller using a state machine for controlling the
10 contention state, the state machine including a grant pending absent state in which the customer
11 premises equipment is polled with a unicast request slot, wherein during the grant pending absent
12 state, the customer premises equipment sends no upstream data to the base station controller but
13 can use the unicast request slot to request a data slot for sending upstream data to the base station
14 controller.

15
16 10. Customer premises equipment as in claim 9, wherein the state machine
17 further includes an idle state in which the customer premises equipment awaits arrival of data
18 packets to send as upstream data to the base station controller.

19
20 11. Customer premises equipment as in claim 10, wherein the state machine
21 further includes a deferring state in which the customer premises equipment requests grant of a
22 data slot for sending upstream traffic to the base station controller and if necessary defers
23 contending for the data slot so as to avoid collisions with other customer premises equipment.

24
25 12. Customer premises equipment as in claim 11, wherein the state machine
26 further includes a grant pending state in which the customer premises equipment awaits and

1 receives grant of the data slot for sending upstream data to the base station controller and sends
2 upstream data to the base station controller after grant of the data slot.

3
4 13. Customer premises equipment as in claim 12, wherein in the grant pending
5 state, the customer premises equipment uses piggybacking to request grant of a next data slot
6 while sending upstream data to the base station controller.

7
8 14. Customer premises equipment as in claim 12, wherein the state machine
9 enters the deferring state upon arrival of data packets to send as upstream data to the base station
10 controller,

11 wherein the state machine enters the grant pending state after the deferring state,
12 returns to the deferring state if a collision occurs, and remains in the grant pending state when
13 sending upstream data to the base station controller with piggybacking, and

14 wherein the state machine enters the grant pending absent state after the customer
15 premises equipment has sent upstream data to the base station controller in the grant pending
16 state.

17
18 15. Customer premises equipment as in claim 14, wherein the state machine
19 further includes an unsolicited grant pending state in which the customer premises equipment
20 receives grant of the data slot for sending upstream data to the base station controller and sends
21 upstream data to the base station controller after grant of the data slot, without having requested
22 the data slot.

23
24 16. Customer premises equipment as in claim 15, wherein the state machine
25 further includes an unsolicited grant pending absent state in which the customer premises
26 equipment is polled with the unicast request slot,

1 wherein during the unsolicited grant pending absent state, the customer premises
2 equipment sends no upstream data to the base station controller but can use the unicast request
3 slot to request the data slot for sending upstream data to the base station controller, and
4 wherein the state machine enters the unsolicited grant pending absent state after
5 the customer premises equipment has sent upstream data to the base station controller in the
6 unsolicited grant pending state.

Abstract

A system for controlling a contention state for a communication link between a base station controller and customer premises equipment in point-to-multipoint communication. The contention state is controlled using a state machine. The state machine includes a grant pending absent state in which a unicast request slot is maintained open for use by the customer premises equipment. During the grant pending absent state, the customer premises equipment sends no upstream data to the base station controller but can use the unicast request slot to request a data slot for sending upstream data to the base station controller. Preferably, the state machine further includes an idle state in which the customer premises equipment awaits arrival of data packets to send as upstream data to the base station controller. The state machine preferably further includes a deferring state in which the customer premises equipment defers contending for the data slot so as to avoid collisions with other customer premises equipment. The state machine also preferably includes a grant pending state in which the customer premises equipment awaits and receives grant of the data slot for sending upstream data to the base station controller and sends upstream data to the base station controller after grant of the data slot. In the grant pending state, the customer premises equipment preferably uses piggybacking to request grant of a next data slot while sending upstream data to the base station controller.




FIG. 1




FIG. 2